



Woodburning

ZERO CLEARANCE FIREPLACES
Z 42 • 231 ZC • 241 ZC



Z 42 w/Prairie design screen doors & black grills

Z 42 Series

Z 42 Specifications 2

#231 ZC & #241 ZC Series

#231 ZC & #241 ZC Specifications 6

Woodburning Fireplace Options & Accessories 8

Z 42 & Z 42 CD SPECIFICATIONS

Model	Fuel Option	High	Low	Efficiency
Z 42	Wood	60,000	8,000	63%
Z 42-CD*	Wood	60,000	8,000	63%

*Cast Doors

Canadian approved

Standard Features

- EPA/WA Certified/Non-Catalytic (EPA emissions rate 3.34 g/hr.)
 - High quality pyro-ceram glass 15-1/2" x 28" (Z42) 12" x 14" (Z42-CD)
 - Arched glass valance (Z42)
 - Large burning area - fits up to 22" logs
 - Air-seal 10 ga. steel door (Z42)
 - Twin air-seal cast iron doors (Z42-CD)
 - Adapts to 6" Class "A" HT-Type (2,100") all fuel chimney
 - Zero clearance
 - 10 year limited warranty
 - (2) heat duct knock-outs for optional ducting (#970 kit required)
 - Air-wash system (keeps viewing area cleaner)*
- *Although the air wash system assists in keeping the glass cleaner, regular cleaning and maintenance are required.

Optional Features

- Decorative grills (several styles/finishes available)
- Decorative screen doors (several styles/finishes available) Z42 only
- Fan kit with variable speed (2 - 110 CFM)
- 44" lintel iron
- 6" flexible heat duct kit

Safety

- Tested by Intertek Testing Services (formerly Warnock Hersey) Complies with U.L. 127 - U.L. Standard for Safety, Factory Built Fireplaces (6/98)
- U.L. 127 - 1999/CAN/ULC S610-M98 For US and Canadian Installations
- EPA certified
- Non-catalytic
- Sealed combustion chamber
- Uses 100% outside air for combustion
- High quality pyro-ceram glass

Specifications

- Height - 38"
- Weight - 525 lbs.
- Width - 42"
- 2.98 cu. ft. firebox
- Depth - 26"

Clearances




Within Enclosure Area:

- Unit to back wall 0"
- Unit to side wall 0"
- Duct boots to framing 0"
- Top stand-off to header 0"

Exposed Area:

- Wallboard to faceplate top edge/sides** 0"
- Fuel door to an adjacent sidewall 8"
- Unit front 36"
- Top of fireplace face to an 8" mantel** 12"
- Remote outlet air grill to ceiling 2"

**Refer to the Mantel Projection Chart on pg. 2 of installation manual





Z 42 w/Mission design doors & black grills



Z 42 standard w/black grills



Z 42 w/black diamond doors & black grills

Good for the environment...

For a wood-fired hearth that's at home anywhere, look no further than Kozy Heat's Z 42 EPA Certified Fireplace. Kozy Heat's Z 42 Non-Catalytic fireplace decreases flammable creosote within the chimney by 90%, and burns up to 33% less fuel. The end result is a clean burn, more warmth with less wood. So relax, kick back and enjoy the flames, knowing you've done your part, not just for the environment, but for your fuel budget.



*Z 42 CD (cast doors)
w/black grills*



*Z 42 CD (cast doors)
w/Mission design grills*



*Z 42 CD (cast doors)
w/brushed nickel accent grills*



241 ZC black cast door w/black grills

A fireplace for almost any place...

A perfect fit, for both your space and your lifestyle. These Kozy Heat fireplaces bring you the best of both worlds. Because they're zero clearance, you can install them almost anywhere. Available as a traditional woodburning fireplace with optional gas conversion - whatever your lifestyle demands.

#231 ZC & #241 ZC SPECIFICATIONS

Model	Fuel Option	High BTUs	Efficiency
231 ZC and 241 ZC Wood	Wood	65,000	73%
KLS-2000 Gas Conversion	NG or LP	45,000	-

Standard Features

- Secondary combustion chamber
- High quality Pyro-Ceram™ glass 16 1/2" x 11" (231 ZC) 12" x 14" (241 ZC)
- Air-wash system (keeps viewing area clean)
- Air-seal cast iron doors
- Zero clearance
- Large burning area – fits up to 22" logs
- Adapts to an 8" HT class A insulated chimney
- 10-year limited warranty
- 3.19 cu. ft. firebox

Optional Features

- Three (3) door models available (black, gold or brushed nickel doors - arched door only)
- Outside air kit - closure and non-closure vents available
- Decorative grills (several styles/finishes available)
- Arched door trim - brass
- Arched face trim - brass
- Outer face trim - brass (241 ZC)
- Fan kit (2 - 110 CFM)
- Arched lintel iron
- 8" B-vent heat duct kit
- Expanded metal face (for use with facing material)
- Grill extension
- Ash drawer
- KLS gas log conversion kit

Safety

- Tested by Warnock Hersey and complies with U.L. standard 127 (7/90) and CAN/ULC-S610-M87
- EPA exempt
- Air seal cast iron doors
- Pyro-Ceram™ glass
- Intake and exhaust air dampers
- Uses 100% outside air for combustion



Gas log conversion kit (optional)



Ash drawer (optional)

Chimney Termination


- 8" diameter, class A, 2100°, insulated double-wall metal chimney
- Minimum chimney height - 10'
- Maximum 30° elbows
- Optional 8" B-vent heat ducts - maximum - 10' in any direction (except down, this will cause a heat sink)

Combustion Air Termination


- 4" diameter 30 ga galvanized pipe (minimum thickness)
- Maximum termination - 26'
- Runs up to 10' - pipe size - 4"
- Runs between 10' - 26' - pipe size - 6"
- Elbows - maximum - 3
- Do not terminate into attic or garage
- Clearance 3' below chimney if terminating beside chase

Clearances

- Unit back to wood enclosure - 1/2"
- Unit sides to wood enclosure - 1/2"
- Unit door to an adjacent wall - 16"
- Heat vents to ceiling - 10"
- Flooring (hearth)
 - Depth - front of fuel opening (non-raised hearth) - 24"
 - front of fuel opening (raised hearth 8") - 16"
 - Width - from sides of fuel opening - 8"
 - from heat duct - 8" vents - 2"
- Top of grill opening to mantel using both 8" heat ducts - 6" not using 8" heat ducts - 11"



#231 ZC Model
Weight - 542 lbs.



#241 ZC Model
Weight - 542 lbs.



231 ZC black door w/black grills



*231 ZC brushed
nickel door w/nickel grills*




231 ZC gold door w/brass grills

FIREPLACE OPTIONS & ACCESSORIES


Z 42 Doors



Black onyx Mission design



Brushed nickel diamond pattern




Antique copper oval pattern

*These decorative doors are for use with model #Z 42 single door only.
The above door styles are available in the three finishes shown, only black contains screen.*



Black Prairie screen door



Black screen door



Moose pattern



Deer w/broken tree pattern

231 ZC Doors



Gold door



Black door




Brushed nickel door

Three door models available - Arched door only

Grill Sets




Brass grills




Brass accent grills




Brushed nickel grills



Brushed nickel accent grills



Mission design grills (Z 42 only)



Prairie design grills (Z 42 only)

Black, chrome and chrome accent grills not shown



For complete information and installation instructions, contact your Kozy Heat Dealer at:

Manufactured by Hussong Mfg. Co. Inc.
204 Industrial Park Drive, Lakefield, MN 56150
Phone 1-800-253-4904 www.kozyheat.com

In order to continually provide the highest quality product available, specifications and dimensions are subject to change. Refer to the unit installation manual for complete installation instructions. Installation must conform with local building codes.